

Turn your dream into reality



TU2200



TU2500L



TTU2700/5

The classic American line

7'
6'
5'
4'



TU1000
\$5,850



TU1450/1
TU1450T/1
\$7,650
\$8,100



TU2200
TU2200T
\$7,950
\$8,450



TU2200/1
TU2200T/1
\$10,800
\$12,200



TU2500L
TU2500LT
\$14,850
\$16,100



TU2700/4 XL
\$11,400



TTU2700
\$13,450



TTU2700/75 XL
TTU2700/5
\$14,550
\$15,900



TLU2000/91
LRU2000/93
\$12,550
\$12,850



TLU2450/1
\$15,800

Warm regards,





Classic American line

Technical Information		Retail Price	Weight	Footprint		Firebox		Wood Length	Load per Firing	Maximum Heat Output*
				Width	Depth	W	D			
		USD	lb	in.	in.	in.	in.	in.	lb	Btu
Small Models										
TU1000	4' height, base vent	\$5,850	2,340	33.1	18.9	12.2	9.6	10-11	19	10,000
TU1000T	5' height, top vent	\$7,200	2,980	33.1	18.9	12.2	9.6	10-11	24	12,500
TU1450/1	5' 3" height, base vent	\$7,650	2,940	35.4	18.9	12.2	9.6	10-11	24	12,000
TU1450T/1	5' 3" height, top vent	\$8,100	2,940	35.4	18.9	12.2	9.6	10-11	24	12,000
Mid-Sized Models										
TU2200	5' height, base vent	\$7,950	3,900	40.2	23.6	15.7	14.4	14-15	31	16,500
TU2200T	5' height, top vent	\$8,450	3,960	40.2	23.6	15.7	14.4	14-15	32	16,000
TU2200/1	5' height, base vent, rough stones	\$10,800	4,570	42.5	23.6	15.7	14.4	14-15	37	19,500
TU2200T/1	5' height, top vent, rough stones	\$12,200	4,570	42.5	23.6	15.7	14.4	14-15	37	18,500
TU2200T/51	6' height, top vent	\$9,950	4,660	40.2	23.6	15.7	14.4	14-15	37	19,000
TU2500L	6' height, base vent, rough stones	\$14,850	5,380	42.5	23.6	15.7	14.4	14-15	43	22,000
TU2500LT	6' height, top vent, rough stones	\$16,100	5,380	42.5	23.6	15.7	14.4	14-15	43	22,000
TLU2000/91	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$12,550	4,580	36.6	29.5	14.4	12.0	12-13	37	19,500
TLU2000/93	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$12,850	4,760	36.6	29.5	14.4	12.0	12-13	38	20,000
Large Models										
TTU2700/4 XL	6' height, top vent	\$11,400	5,970	40.2	29.5	15.7	19.7	14-18	48	23,000
TTU2700/75 XL	7' height, 16.5" x 17.1" bakeoven, top vent	\$14,550	6,710	40.2	29.5	15.7	19.7	14-18	54	26,000
TTU2700	7' height, see-through firebox, top vent	\$13,450	6,540	40.2	29.5	15.7	24.8	14-18	52	25,000
TTU2700/5	7' height, see-through firebox, 16.5" x 17.1" bakeoven, top vent	\$15,900	7,200	40.2	29.5	15.7	24.8	14-18	58	28,000
TLU2450/1	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$15,800	6,600	42.5	35.4	15.7	14.4	14-15	53	26,000
Optional Features (selection)										
TU2200Bench	Soapstone two-sided bench for TU2200 (adds 2 3/8" to height)	\$1,265	460	68.5	27.8					
2700/6	Soapstone four-sided bench for TTU2700	\$3,690	1,790	63.8	53.1					
M10L	Tulikivi Classic soapstone tiles, per square foot	\$18	5	11.8	11.8					
5123	Electric elements 2 kW	870	6							

***Maximum heat output is based on two firings per day, at least 10 hours apart.**

Delivery and on-site assembling are not included in the Retail Price. Heat shields, hearth tiles, benches & other accessories are available as optional features.

Tulikivi heaters are high thermal mass appliances and require appropriate structural support. Being a naturally occurring material, soapstone can vary in aspect and weight.

5 years Warranty. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification.

Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise.

Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield.

Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front of the heater.

