

Turn your dream into reality



## The modern American line



Warm regards,





## Modern American line

Technical Information		Retail Price	Weight	Footprint		Firebox		Wood Length	Load per Firing	Maximum Heat Output*
				Width	Depth	W	D			
		USD	lb	in.	in.	in.	in.	in.	lb	Btu
<b>Small Models</b>										
TU1000/50 Grafia	4' height, base vent, Grafia texture	\$6,550	2,200	33.1	18.9	12.2	9.6	10-11	18	9,500
TU1000T/50 Grafia	5' height, top vent, Grafia texture	\$8,100	2,880	33.1	18.9	12.2	9.6	10-11	23	12,000
TU1000/92	5' height, base vent	\$7,400	2,690	33.1	18.9	12.2	9.6	10-11	22	11,000
TU1000T/92	5' height, top vent	\$7,700	2,880	33.1	18.9	12.2	9.6	10-11	23	12,000
<b>Mid-Sized Models</b>										
TU2200/92	5' height, base vent	\$8,150	3,900	40.2	23.6	15.7	14.4	14-15	31	16,500
TU2200T/92	5' height, top vent	\$8,900	4,090	40.2	23.6	15.7	14.4	14-15	33	16,500
TU2200/50 Grafia	5' height, base vent, Grafia texture	\$9,100	3,980	40.2	23.6	15.7	14.4	14-15	32	17,000
TU2200T/50 Grafia	5' height, top vent, Grafia texture	\$9,450	3,980	40.2	23.6	15.7	14.4	14-15	32	16,500
TLU2000/92	5' 5" height, 15.4" x 18.3" bakeoven, base vent	\$11,500	4,320	36.6	27.2	14.5	12.0	12-13	35	18,500
TLU2000/94	5' 5" height, 15.4" x 18.3" rear-facing bakeoven, base vent	\$11,750	4,340	36.6	27.2	14.5	12.0	12-13	35	18,500
TLU2000/50 Grafia	5' 5" height, 15.4" x 18.3" bakeoven, base vent, Grafia texture	\$11,900	4,300	36.6	27.2	14.5	12.0	12-13	34	18,000
<b>Large Models</b>										
TTU2700/8 XL	6' height, top vent	\$11,550	6,140	40.2	29.5	15.7	19.7	14-18	49	24,000
TLU2450/92	5' 6" height, 17.7" x 21.9" bakeoven, base vent	\$14,000	5,730	42.5	35.4	15.7	14.4	14-15	46	22,500
<b>Optional Features (selection)</b>										
M10L	Tulikivi Classic soapstone tiles, per square foot	\$18	5	11.8	11.8					
5123	Electric elements 2 kW	870	6							

**\*Maximum heat output is based on two firings per day, at least 10 hours apart.**

Delivery and on-site assembling are not included in the Retail Price. Heat shields, hearth tiles, benches & other accessories are available as optional features.

Tulikivi heaters are high thermal mass appliances and require appropriate structural support. Being a naturally occurring material, soapstone can vary in aspect and weight.

5 years Warranty. Tulikivi heaters must be assembled on site by a Tulikivi installer. They are UL/ULC safety tested & listed and don't require EPA certification.

Chimney: 20' minimum height from floor for models with bakeovens, 15' otherwise. Recommended flue dia.: 6" or 7" for small models, 7" or 8" otherwise.

Clearances to combustibles: 20" to back, 14" to sides, 10" to top and 48" to front. Those can be reduced to 3" with a Tulikivi specified heat shield.

Floor protection: 3/8" min. thickness of non-combustible material, extending 8" from sides, 8" from back (unless a heat shield is used) and 16" from front of the heater.

modified May 6, 2018

